

United States Patent Application

For

A METHOD OF PERFORMING BACK-END MANUFACTURING OF AN  
INTEGRATED CIRCUIT DEVICE

Inventors:

THURMAN J. RODGERS  
BO SOON CHANG

Prepared by:  
WAGNER, MURABITO & HAO LLP  
Two North Market Street  
Third Floor  
San Jose, California 95113

# A METHOD OF PERFORMING BACK-END MANUFACTURING OF AN INTEGRATED CIRCUIT DEVICE

## RELATED UNITED STATES APPLICATION

5           This application claims priority to the provisional United States Patent Application, Serial Number 60/272,283, Docket CYPR-PM01008.PRO, entitled "Automated and/or Integrated Process and/or Equipment for Assembling, Packaging, Finishing, and/or Testing," filed February 27, 2001, and assigned to the assignee of the present application which is hereby incorporated by reference.

## FIELD OF THE INVENTION

10           The present invention relates to the field of IC chip manufacturing. More particularly, embodiments of the present invention relate to a method of back-end manufacturing IC packaged chips using an integrated automated back-end IC  
15 manufacturing assembly.

## BACKGROUND ART

20           Conventional back-end IC manufacturing facilities, at contract assembly houses as well as several original equipment manufacturers (OEMs), have a moderate to low level of automation and equipment integration. These lines typically require several manual steps and depend upon operator intervention for many, if not nearly all, operation, maintenance, lot management and inspection steps. Since this is typically a batch type process, there maybe a high level of work-

in-progress (WIP) inventory, as well as relatively high cycle times. This type of factory management may not be suitable for manufacturing where flexibility is key, and daily operation may require several changeovers in die, package and leadframe types.

5

Presently, the back-end manufacturing process for ICs (i.e. from manufactured wafer to tested and packaged die) is labor intense. In order to manufacture an IC chip, in the back-end, from the initial step of wafer reception to the packaging and shipping of the finished chip, there are many personnel and specialized pieces of equipment involved. Further, the process of back-end manufacturing an IC chip is a relatively long one. The complete process typically takes anywhere from four to six weeks to obtain a final packaged chip, and generally takes on the order of 1.5 to 2 weeks when using special "rush" or "hot lot" procedures.

10  
15

Due to the length of the back-end manufacturing process and the required manpower, IC (IC) chips are generally manufactured in batches. That is, the process of back-end manufacturing a single IC is done on a large scale with individual large batches running through discrete process steps. This large scale is utilized to add a standard of efficiency to an otherwise complex process. For instance, a wafer that is received from an outside vendor is cut into strips. Each strip may contain approximately 200 die, and there may be 50 strips in a batch. Therefore, a typical

20

batch of ICs, formed through a single back-end IC manufacturing process, may contain 10,000 or more IC chips.

An embodiment of a conventional batch-oriented back-end IC manufacturing process is illustrated in Figure 1. This embodiment illustrates the length of a conventional back-end IC manufacturing process. Batches of chips move from one stage of the process to the next. In block diagram 100, the back-end manufacturing line includes front-of-line portion 100A, end-of-line portion 100B, test 128, and finish portion 100C. The back-end IC manufacturing process begins with die attach station (D/A) 110. Although a die preparation process is required, this is typically done outside front-of-line portion 100A. Furthermore, the die preparation process may take place in a different location than the rest of the back-end IC manufacturing process.

Front-of-line portion 100A includes die attach station (D/A) 110, cure station 112, plasma treatment station 114, wire bond station (W/B) 116, and another plasma station 118 (typically a plasma cleaning station). This back-end IC manufacturing process includes many aspects which require human material handling stations (HM) 150. HM 150 steps are represented in Figure 1 with arrows. These HM 150 steps include transferring the batch from one step of the process to the next, as well as between specific manual visual inspection stations (MVI) 105.

In the front-of-line portion 100A, the cure station 112 may carry out a curing process in a machine designed to heat a batch of strips to a temperature of about 150 degrees Celsius, for a period of one hour, in order to cure the glue used in the die attach step. This cure station 112 is followed by a plasma station 114 cleaning step utilizing oxygen (O<sub>2</sub>) or Argon (Ar). The next step is wire bond station (W/B) 116 followed by MVI 105. Another plasma station 118 cleaning step is done following wire bond station (W/B) 116 and another MVI 105. The plasma station 118 cleaning step is similar to plasma station 114 cleaning step, and each plasma step may last anywhere from 30 minutes to one hour.

With reference still to Figure 1, back-end manufacturing line 100 continues with an end-of-line portion 100B where need for human interaction also exists. End-of-line portion 100B begins with mold station 120. HM 150 is utilized to move the batch through each MVI 105. The next step in end-of-line portion 100B is post mold cure station (PMC) 122. PMC 122 is a curing step which requires a temperature of 175-degree Celsius and a timeframe of approximately 5 hours. After PMC 122, the strip undergoes solder ball attach station (SBA) 124. Following SBA 124, MVI 105 takes place to ensure proper attachment of the ball to each strip in the batch. The batch is then processed through saw station 126. Saw station 126 separates the batch into individual IC chips. The final step in end-of-line portion 100B is MVI 105 of the completed saw station 126 step. Throughout the back-end manufacturing

process, MVI 105 normally includes additional quality control and assurance measures.

Following the completion of end-of-line portion 100B, back-end  
5 manufacturing line 100 continues with test portion 128. In test portion 128, as illustrated in the previous portions, the need for human interaction includes human handling during both the testing, and inspecting phases.

10 With reference still to Figure 1, back-end manufacturing line 100 further illustrates the final portion of the back-end IC manufacturing process. The final portion is illustrated as finish portion 100C. Finish portion 100C includes mark station 130, dry bake station 132, and tape and reel station (T/R) 134. Most significantly, dry bake station 132 is a 24-hour dry bake step performed prior to T/R 134. Dry bake station 132 is required by modern back-end IC manufacturing  
15 processes in order to meet the stringent moisture sensitivity level (MSL) 3 IC chip packaging requirements. Specifically, MSL 3 is a moisture level benchmark that meets demanding requirements placed on back-end IC manufacturers.

Therefore, in a typical back-end IC manufacturing line, a production cycle  
20 may span a period of four to six weeks. Moreover, the processing cycle may be done at the batch level which results in approximately 10,000 or more IC chips per stage. This batch level process results in a large inventory of on hand IC chips. In an effort

to control production overruns, a manufacturer will normally use a build-to-forecast model based on contract back-end IC manufacturing techniques.

Disadvantages of the batch level process include the large minimum order size and the long timeframe for the manufacture of a specific type of IC. For example, if a customer requests an uncommon or highly demanded type of IC, e.g., one that is not in inventory, they would typically place a special order. In this case, a small order may not be economically worthwhile. Specifically, the batch level process is generally cost prohibitive unless the customer orders a specified minimum amount of product. Further, it generally takes a minimum of four to six weeks to process a special order. Moreover, this minimum time conventionally includes time to reset and/or maintain machinery, and/or instruct inspectors on expected differences in the back-end IC manufacturing process.

Another disadvantage of the conventional batch process is the multitude of procedures using human interaction with the batch in transporting the batch from stage to stage, or during certain stages, such as visual inspection (HM). These procedures include MVI, quality assurance (QA), and handling throughout the entire back-end IC manufacturing process. Specifically, MVI typically involves a pause in the back-end IC manufacturing process so that an operator can manually inspect the IC chip after a given step. MVI is done to ensure correct part placement, proper IC shape, elimination of excess material on the IC, etc. MVI, however, is

error prone because it relies on human judgment and discrimination, and it may be tedious, and may require sustained or prolonged concentration, thereby introducing difficult practice for periods of time in excess of an hour or two, or over an entire workday.

5

Further, upon completion of the visual inspection, a QA examination takes place to ensure the MVI was done correctly. This QA examination further delays the back-end IC manufacturing process due to an increase in overall time spent on the redundant inspection. Another detrimental aspect of the MVI process is the human handling of the strips in the batch. As an inspector analyzes a die on a strip in the batch, they may inadvertently cause a defect. Thus, an inspector looking for defects may actually be creating them.

A further problem arises in batch back-end IC manufacturing in that a relatively large number of personnel are required, e.g., personnel to move the batch from point to point, personnel for MVIs, personnel for QA inspections, and personnel to operate each of the many processes required in typical IC back-end IC manufacturing. The average processing line may easily maintain a payroll of thirty-plus personnel. Therefore, the expense required per employee must be factored into the final cost of the IC chip.



Early efforts in equipment integration and automation result in “islands of automation” involving some automation at an individual equipment level, but not a high level of multi-equipment integration. Individual operation steps at the level of an individual piece of equipment had been automated to some degree, but still manual inspection, as well as manual lot movement and tracking remained typical. Further improvements in equipment and software capabilities have transitioned these islands to automation cells that handle large chunks of the assembly process. Each cell is a functional area and represents part of the total operation. However, a total solution has not been presented heretofore.

## SUMMARY OF INVENTION

Thus, a need exists for a method to integrate an IC back-end manufacturing assembly. A further need exists for a method to integrate an IC back-end manufacturing assembly, which can proficiently perform IC back-end manufacturing on a smaller scale of chips. A further need exists for a method to integrate a back-end IC manufacturing assembly which can abbreviate the MVI and QA process while maintaining a higher quality of visual inspection. Still another need exists for a method to integrate an IC back-end manufacturing assembly which requires fewer personnel to maintain a back-end manufacturing line. A further need exists for a method to integrate an IC back-end manufacturing assembly which is compatible with existing IC back-end manufacturing processes.

One embodiment of the present invention advances factory automation by implementing an advanced, fully integrated assembly and test lines capable of back-end manufacturing ball grid array (BGA) packages (for example, molded BGA packages in a matrix array). The implementation has integrated the back-end manufacturing process from die attach to tape and reel, with a reduced cycle time. This implementation enables a virtually "hands-free" production line with automated chip movement, testing, inspection and sorting as well as automated chip assembly.

The present invention provides, in various embodiments, methods to integrate an IC chip back-end manufacturing assembly. Embodiments of the present invention also provide an integrated in-line IC back-end manufacturing assembly process, which proficiently performs IC back-end manufacturing on a smaller scale.

5 The present invention further provides a method to integrate an IC back-end manufacturing assembly, which reduces the human-operated MVI and QA processes while maintaining a higher quality of visual inspection. The present invention also provides a method to integrate an IC back-end manufacturing assembly which requires fewer personnel on the back-end manufacturing line. The present invention further provides a method to integrate an IC back-end manufacturing assembly, which is compatible with existing IC back-end manufacturing processes.

10  
15  
20 Generally, an embodiment is directed to an integrated assembly process that automatically moves small amounts of IC chips (e.g. a die strip) through packaging stages that span from receiving the IC dies to testing the packaged chip and tape and reel assembly. Herein, the processing of IC chips in a pipeline fashion is called "in-line" assembly because the individual chips (in small amounts) are moved from station to station very rapidly and are not delayed in batch fashion. In-line assembly is different from batch processing, in that, small amounts of chips move through the entire assembly process of the present invention (in a pipeline fashion) from one end to another without interruption or delay associated with batch processing.

Handling, testing and processing the chips are also automated processes in accordance with the present invention to reduce and/or eliminate human interactions.

5 Specifically, in one embodiment, the present invention processes a die-strip through a front-of-line assembly portion which comprises a plurality of sub-stations (e.g. in-line die attach, in-line cure, in-line plasma, in-line wire bond, and another in-line plasma) operating on an in-line basis. The die-strip is then automatically provided to an end-of-line assembly portion. The die-strip is then processed through an end-of-line assembly portion which comprises a plurality of sub-stations (e.g. in-line mold, in-line PMC, in-line SBA, in-line saw and in-line sort) operating on an in-line basis. The present embodiment then automatically provides the die-strip to an in-line test assembly portion. The die-strip components are then tested by the test portion and then automatically provided to a finish assembly portion. The present embodiment then processes the die-strip components through the finish portion which comprises a plurality of sub-stations (e.g. marking, final visual inspection, and tape and reel) operating on the die components. Therefore, substations of the integrated assembly line of the present invention process IC chips using an in-line approach.

20 In one embodiment, the various substations of the integrated in-line IC back-end manufacturing hardware are arranged in an assembly line format. Further, a

software process monitors and controls the integrated in-line IC back-end manufacturing hardware. It is also appreciated that an automated reject management protocol is implemented from initial die attach through test and finish. Specifically, the reject management protocol maintains a strip process history which is updated via an electronic strip map database 620 throughout the back-end manufacturing process using comprehensive strip level tracking procedure. The updates to the electronic strip map database 620 are received through a network hierarchy including automated visual camera technology, integrated cell controllers, and an overall back-end manufacturing execution system. These elements virtually eliminate human manual intervention in the inspecting, testing and sorting of IC chips.

In one embodiment, a universal packaging process is applied to the in-line assembly line back-end manufacturing process. Specifically, universal packaging utilizes the in-line subassemblies in conjunction with the integrated software processes to increase throughput time of a specific package size. A further benefit is realized with the streamlined transition of subassembly back-end manufacturing specifications from one package size to another. In general, aspects of universal packaging allow package changeovers with minimal changeover times, thus allowing some amount of flexibility within package families. For example, in one embodiment, an exemplary changeover in the entire line from a 7mm x 7mm package to any other package size may take less than thirty minutes.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention:

5

CONVENTIONAL ART FIGURE 1 is a block diagram illustrating a conventional batch processed IC back-end manufacturing line.

FIGURE 2 is a block diagram illustrating an exemplary integrated in-line IC back-end manufacturing assembly line and assembly method in accordance with one embodiment of the present invention.

FIGURE 3A is a block diagram illustrating an exemplary front-of-line portion of the novel integrated in-line IC back-end manufacturing line and method in accordance with one embodiment of the present invention.

FIGURE 3B is a block diagram illustrating an exemplary end-of-line portion of the novel integrated in-line IC back-end manufacturing line and method in accordance with one embodiment of the present invention.

20

FIGURE 3C is a block diagram illustrating an exemplary finish portion of the novel integrated in-line IC back-end manufacturing line and method in accordance with one embodiment of the present invention.

5        FIGURE 4 is a block diagram illustrating an exemplary electronic die-strip map database in accordance with one embodiment of the present invention.

FIGURE 5 is a block diagram of an exemplary process of an electronic inspection and die-strip map database updating method in accordance with one embodiment of the present invention.

FIGURE 6 is a block diagram of exemplary reject management system in accordance with one embodiment of the present invention.

10  
15        FIGURE 7 is a block diagram illustrating an exemplary reject management and sorting system in accordance with another embodiment of the present invention.

FIGURE 8 is a flow chart of steps in an exemplary method for processing a  
20    chip through integrated in-line IC back-end manufacturing hardware in accordance with one embodiment of the present invention.

FIGURE 9 is a flow chart of steps for software integration in accordance with one embodiment of the present invention.

FIGURE 10 is a flow chart of steps for reject management protocol used in  
5 conjunction with the in-line integrated in-line IC back-end manufacturing assembly in accordance with one embodiment of the present invention.

FIGURE 11 is a flow chart of steps in an exemplary method for universal packaging in accordance with one embodiment of the present invention.

FIGURE 12 is a block diagram of an exemplary general purpose computing system in accordance with one embodiment of the present invention.

FIGURE 13 is a block diagram of an exemplary method of electronic  
15 inspection and strip map database updating in accordance with another embodiment of the present invention.

The drawings referred to in this description should be understood as not being drawn to scale except if specifically noted.



## DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. While the invention will be described in conjunction with the preferred embodiments, it will be understood that they are not intended to limit the invention to these 5 embodiments. On the contrary, the invention is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the invention as defined by the appended claims. Furthermore, in the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be obvious to one of ordinary skill in the art that the present invention may be practiced without these specific details. In other instances, well-known methods, procedures, components, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present invention.

Moreover, some portions of the detailed descriptions which follow are presented in terms of procedures, logic blocks, processing and other symbolic representations of operations for fabricating IC structures. These descriptions and representations are the means used by those skilled in the art of IC fabrication to 20 most effectively convey the substance of their work to others skilled in the art. In the present application, a procedure, logic block, process, or the like, is conceived to be a self-consistent sequence of steps or instructions leading to a desired result.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise, as apparent from the following discussions, it is appreciated that throughout the present invention, discussions utilizing terms such as "establishing," "coupling," "monitoring," and "utilizing," or the like, refer to actions and processes (e.g. Figures 2-13) of IC back-end manufacturing.

## OVERVIEW

Back-end IC manufacturing, in one example, refers to IC packaging and other assembly functions performed typically at or past "front-of-line" assembly time. This may include, "front-of-line" assembly, "end-of-line" assembly, "test", and/or "finish" assembly.

Embodiments of the present invention concern an integrated, software-driven, in-line module for assembling, testing and /or finishing ICs (IC's) that, in one embodiment, contains multiple substations, e.g., machines, from die attach through tape and reel (in one embodiment having a length of about 120 feet), connected with cell controllers to a higher level manufacturing execution system (MES) and factory planning information. In effect, the system works like a single assembly-test-finish equipment integrating all the individual processes into one assembly step using software and hardware integration. All this integrated

equipment allows a rapid package changeover with similar package size families, allowing flexibility in production capabilities.

The present embodiment advantageously uses automated strip conveyor systems and robotic arms. In one embodiment, there is no human handling of substrate strips or IC units at all, and all human inspection, either offline or online, may be replaced with machine auto-vision. In addition to better inspection quality, machine auto vision also allows quality assurance (QA) simultaneously with production. The present embodiment simplifies the overall assembly process by eliminating offline processes and/or reducing in-line batch processes like curing, plating, and dry baking (e.g. converting such batch processes to continuous processes).

In one embodiment, the exemplary platform package may be a matrix array “die-strip” (e.g. an n-by-m matrix array of die on a single substrate, where n and m are each independently an integer of  $\geq 2$  preferably from 3 to 15, more preferably from 4 to 10) molded ball grid array (BGA) package. Array-based package-independent processing lends itself to the goals of automation and integration..

## INTEGRATED HARDWARE

In the following discussion, Figures 2-8 illustrate the hardware integration process of the present embodiment broken into four assembly portions. Including front-of-line, end-of line, test, and finish.

5

Figure 2 is a block diagram illustrating an integrated in-line IC back-end manufacturing assembly (process) 200 in accordance with one embodiment of the present invention. Figure 2 begins with the die attach (D/A) substation 304 that performs the D/A process and ends with tape and reel assembly 328. Any die preparation processes may be used with the present embodiment.

Figures 3A-3C are block diagrams illustrating more detailed versions of line 200 of Figure 2. Specifically, Figure 3A is front-of-line assembly portion 300A, Figure 3B is end-of-line assembly portion 300B, and Figure 3C is finish assembly portion 300C.

Figure 8 is a flow diagram for illustrating pertinent process steps associated with line 200. With reference now to step 802 of Figure 8 and to Figure 3A, the present embodiment processes die-strip 400 through front-of-line assembly portion 300A. As described above, the implementation of a single die-strip 400 traveling through line 200, allows for a more personal approach to the back-end manufacturing process. Specifically, since only a single die-strip 400 is processed

through each substation, an order may be placed for a number of IC chips which is smaller than the conventional art batch size without ensuing the extraordinary costs previously associated with a small run. It is also relevant that the difference in size between a single die-strip 400 and a batch containing 50 or so die-strips, enables smaller more efficient machinery to be utilized during line 200. In general, the present embodiment processes die-strip 400 individually in an in-line fashion. Therefore, the batch process used by the conventional art is removed from the integrated in-line IC back-end manufacturing method of the present embodiment.

Now, with reference to step 802 of Figure 8 and Figure 3A, the front-of-line assembly portion 300A comprises a plurality of sub-stations operating on an in-line basis. In one embodiment, the plurality of sub-stations include die attach substation (D/A) 304, cure substation 306, plasma substation 308, wire bond substation (W/B) 310, and plasma substation 312. In the present embodiment, many portions of the conventional line process have been modified in order to establish an in-line assembly line format.

Front-of-line portion 300A receives a die-strip (an example of a die-strip 400 is illustrated in Figure 4) at the die attach substation 304 that performs the die attach (D/A) process. However, the actual cutting and shaping of the wafer, from which die-strip 400 is formed, may take place outside of the scope of the present embodiment.

Substation 304 performs the initial processes of attaching die to a strip thereby forming a die-strip 400. Specifically, D/A substation 304 attaches a die (for example, a BGA die) to die strip 400 (Fig. 4). In the present embodiment glue is used to attach die to die strip 400. The glue may be any glue utilized by one skilled in the art. It is appreciated that any well-known die preparation process may be used with the present embodiment.

The second step in front-of-line assembly portion 300A is performed by cure substation 306 that performs the cure process. In general, cure substation 306 performs an in-line process for drying the adhesive between die and substrate used in D/A substation 304. That is, die strip 400 remains at cure substation 306 until the glue is cured and die is fixedly coupled to die strip 400. The third step is plasma substation 308 that performs a plasma process. Specifically, plasma substation 308 performs an in-line cleaning substation that is applied to both sides of die strip 400 in order to clean any excess glue from die and die strip 400. In general, in-line plasma substation 308 may utilize any number of well-known cleaning processes.

The forth step in front-of-line assembly portion 300A is performed at W/B substation 310. W/B substation 310 performs an in-line process for wire bonding die strip 400. The final step in front-of-line assembly 300A is performed by plasma substation 312. Plasma substation 312 performs an in-line cleaning process applied

to both sides of die strip 400 in order to clean any excess wire bonding material from die strip 400.

With further reference to step 802 of Figure 8 and Figure 3A, the present embodiment reduces most processing times established by the sub-stages of the conventional art. For instance, in the present embodiment, cure process and substation 306 is a snap cure which takes approximately 2 minutes. In addition, both plasma cleaning processes and substations (e.g. plasma substation 308 and plasma substation 312) have been reduced in length to approximately one minute. The reductions in processing time are a result of both the reduced processing size and in-line nature of the present embodiment. That is, since the present embodiment is applied at a die-strip 400 level and since each die-strip 400 is maintained in a controlled environment, many time consuming steps of the conventional art batch process have been reduced. Specifically, the internal areas of the in-line processing stations are reduced significantly. This reduction results in less time required for heating, venting, vacuuming, etc. Further, with no need for human interaction, the processing environment may be maintained at peak proficiency.

With further reference to step 802 of Figure 8 and Figure 3A, in the present embodiment human handling situations have been removed. This removal of human interaction is obtained by the implementation of specific back-end manufacturing aspects. The first aspect is the integration of the hardware.

Specifically, the integration of an in-line assembly process results in automated movement of die-strip 400 from one process to the next. The second aspect is the introduction of vision camera systems (V/C) 302 at D/A substation 304 and W/B substation 310. Specifically, V/C 302 assumes all aspects of the inspection and QA requirements previously performed by hand. Further details of V/C 302 are covered in the software process outlined herein.

With reference now to step 804 of Figure 8 and Figure 2, the present embodiment automatically, in an in-line fashion, provides die-strip 400 from the front-of-line assembly portion 300A to an end-of-line assembly portion 300B. Analogous to the front-of-line assembly portion 300A, the end-of-line assembly portion 300B contains many in-line substations. Also, as illustrated in the previous front-of-line assembly portion 300A, need for human interaction within the back-end manufacturing process is eliminated.

With reference now to step 806 of Figure 8 and Figure 3B, the present embodiment processes die-strip 400 through the end-of-line assembly portion 300B having a plurality of sub-stations operating on an in-line basis. In one embodiment, the plurality of sub-stations in end-of-line assembly portion 300B include mold substation 314, post mold cure (PMC) substation 316, solder ball attach (SBA) substation 318, saw substation 320, and sort substation 322.



The first process in end-of-line assembly portion 300B is performed at the mold substation 314. In general, mold substation 314 utilizes a molding compound injection. Specifically, mold substation 314 is an in-line process that places a protective layer of material above die strip 400. In the present embodiment mold substation 314 may be a plastic or any other type of non-conductive material which can act as a layer of protection.

The second step in end-of-line assembly portion 300B is performed by the PMC substation 316. In general, PMC substation 316 performs an in-line process for drying the non-conductive material used at mold substation 314. That is, die strip 400 remains at PMC substation 316 until the molding material is cured, thereby ensuring that die is protectively covered on die strip 400.

The third step in end-of-line assembly portion 300B is performed at the SBA substation 318. Specifically, SBA substation 318 performs an in-line process for attaching a solder ball to die strip 400. The forth step in end-of-line assembly portion 300B is performed at the saw substation 320. Saw substation 320 performs an in-line process for cutting die strip 400. Specifically, saw substation 320 cuts die strip 400 into single components each containing a die portion.

The final step in end-of-line assembly portion 300B is performed at the sort substation 322. Sort substation 322 performs an in-line sorting process applied to

each component cut from die strip 400. In general, sort substation 322 is used for separating e.g., categorizing, individual die components into accepted and rejected piles. The specifics of saw substation 320 and sort substation 322 are discussed in more detail herein. At the completion of end-of-line portion 300B, die components are provided to the tester substation 330 (Fig. 2).

With further reference to step 806 of Figure 8 and Figure 3B, the present embodiment both reduces and modifies most processes and times established by the conventional art, thereby allowing an efficient in-line assembly to be performed. Of particular significance, PMC substation 316 has been integrated into in-line IC back-end manufacturing line 200. Not only has PMC substation 316 been integrated into the back-end manufacturing methodology of the present embodiment, it is used to accomplish both PMC 122 and dry bake 132 of the conventional art. Additionally, PMC substation 316 includes an annealing portion (e.g. for approx. 20 minutes) to reduce strip warpage and allow mechanical stress relief. Therefore, in the present embodiment, upon completion of a 175 degree Celsius, 5 hour PMC substation 316, die strip 400 does not require a dry bake 132. Although dry bake 132 has been removed, the resulting components are nevertheless packaged at moisture sensitivity level 3 (MSL 3). Specifically, the ability to remove dry bake 132 is due to the extremely short cycle time of line 200 following PMC substation 316. In fact, the removal of dry bake 132 advantageously reduces line 200s timeline by at least 24 hours.

Referring still to step 806 of Figure 8 and Figure 3B, the present embodiment establishes new methods for saw substation 320. Generally speaking, conventional saw machines were designed for 8" wafer sawing. However, the present embodiment employs n-by-m matrix array strips. Therefore, the substrate cutting length on the saw is modified (in one embodiment, to 205 mm). In another embodiment, the package sawing machine may be enhanced to allow tape-less singulation (sawing) of molded strips with a length of more than 230 mm. The present modifications achieve a higher unit density, thereby increasing the throughput of the line.

It is appreciated that V/C systems 302 are employed by the end-of-line portion 300B at the mold 314, SBA 318, and sort 322 substations. The interaction of these systems is described further to follow.

With reference now to step 808 of Figure 8 and Figure 2, the present embodiment automatically provides die-strip components 400 from end-of-line assembly portion 300B to a test assembly portion 330 using an in-line fashion.

With reference now to step 810 of Figure 8 and Figure 2, die-strip components 400 are electronically tested using test assembly portion 330. In general, test assembly portion 330 is a quality assurance measure wherein specific components are tested to ensure proper operation. Specifically, test assembly portion 330 can be used to

identify a good or bad die. It may further be utilized to subdivide good die based on performance characteristics such as speed, thermodynamic values, etc. As previously stated, this is accomplished in an automated in-line fashion.

5 With reference now to step 812 of Figure 8 and Figures 2, the present embodiment automatically provides die-strip components 400 from test assembly portion 330 to a finish assembly portion 300C. As illustrated in the previous portions (e.g. 300A and 300B) the need for human interaction within the back-end manufacturing process has been eliminated.

With reference now to step 814 of Figure 8 and Figure 3C, the present embodiment processes die-strip components 400 through the finish assembly portion 300C, which comprises a plurality of sub-stations operating on an in-line basis. In one embodiment, the plurality of sub-stations in finish portion 300C include mark substation 324, final visual inspection (FVI) substation 326, and tape and reel (T/R) substation 328.

In general, in-line finish portion 300C performs the final processes to the components of die strip 400. The first process of in-line finish assembly portion 20 300C (e.g. performed by mark substation 324) marks the components cut from die strip 400. In the present embodiment the mark is an identifying characteristic enabling the components cut from die strip 400 to be grouped into lots. The mark is

aided by a visual inspection system (e.g. V/C 302) and may further contain a company logo, or any other information the manufacturer may desire.

The second step in in-line finish portion 300C is performed by the FVI substation 326. In general, FVI substation 326 performs an in-line process for performing the final visual inspection on die strip 400 components. That is, components of die strip 400 are visually inspected for many technical aspects. A few inspection requirements include assurance that components are complete, that all parts are properly protected, that the sawing process was completed correctly, etc. In the present embodiment, FVI substation 326 is performed using the aid of an in-line automated visual camera (V/C) 302.

The final step in in-line finish portion 300C is performed by T/R substation 328. T/R substation 328 performs an in-line process for packaging the components cut from die strip 400. T/R substation 328 is covered in more detail in the universal packaging section herein and uses a visual inspection system V/C 302.

In the finish assembly portion 300C, the 24-hour dry bake process of the conventional art has been removed completely. In its place, final visual inspection (FVI) substation 326 occurs. FVI substation 326 utilizes V/C 302 and the integrated software processes of line 200 to inspect the finished components prior to packaging. In one embodiment, packaging is referred to as tape and reel (T/R) substation 328

which places the individual IC chip components into compartments which are taped together and then reeled. The above-mentioned, V/C 302 and integrated software processes will be covered in more detail herein.

5 It is appreciated that embodiments of the present invention utilize a number of automated carriers or conveyors to move die-strips and die-strip components from one substation to another. These conveyors, and the substations themselves, are controlled by a central software application of a computer control system.

10 With reference still to Figure 2, the present embodiment has reduced the overall processing time of a die strip 400 by using a completely in-line technique without human interaction. Specifically, in the conventional art, a production cycle spanned a period of four to six weeks. In the present embodiment, a production cycle takes approximately one day from D/A substation 304 to T/R substation 328.  
15 Further, the processing cycle results in an average of 3,600 units per hour for a 48-pin package. The significant increase in productivity is due to a new die-strip 400 not having to wait for a previous die-strip 400 to finish an entire processing cycle. In fact, a new die-strip 400 may enter line 200 in pipeline fashion, e.g., as soon as the previous die-strip 400 has cleared the initial processing step. Therefore, line 200  
20 maintains an efficient, made-to-order process with die-strips being pipelined through the in-line assembly process. The present embodiment further results in

lower labor costs and reduced personnel requirements due to the automation of the assembly line method.

## INTEGRATED SOFTWARE PROCESS

5           With reference now to Figure 12, portions of the present embodiment are comprised of or controlled by computer-readable and computer-executable instructions which reside, for example, in computer-usable media of a computer control system. Figure 12 illustrates an exemplary computer system 1212 that may be used in accordance with one embodiment of the present invention. It is appreciated that system 1212 of Figure 12 is exemplary only and that the present embodiment can operate on or within, or be controlled by, a number of different computer systems including general purpose networked computer systems, embedded computer systems, routers, switches, server devices, client devices, various intermediate devices/nodes, stand alone computer systems, and the like. Additionally, computer system 1212 of Figure 12 is well adapted having computer readable media such as, for example, a floppy disk, a compact disc, and the like coupled thereto.

          System 1212 of Figure 12 includes an address/data bus 1210 for  
20   communicating information, and a central processor unit 1201 coupled to bus 1210 for processing information and instructions. System 1212 also includes data storage features such as a computer usable volatile memory 1202, e.g. random access

memory (RAM), coupled to bus 1210 for storing information and instructions for central processor unit 1201, computer usable non-volatile memory 1203, e.g. read only memory (ROM), coupled to bus 1210 for storing static information and instructions for the central processor unit 1201, and a data storage device 1204 (e.g., a magnetic or optical disk and disk drive) coupled to bus 1210 for storing information and instructions. System 1212 of the present embodiment also includes an optional alphanumeric input device 1206 including alphanumeric and function keys coupled to bus 1210 for communicating information and command selections to central processor unit 1201. System 1212 also optionally includes an optional cursor control device 1207 coupled to bus 1210 for communicating user input information and command selections to central processor unit 1201. System 1212 of the present embodiment also includes an optional display device 1205 coupled to bus 1210 for displaying information.

With reference now to process 900 of Figure 9, the present embodiment implements a software process 900 in conjunction with assembly line 200. In one embodiment, the software process 900 takes place on computer control system 1212.

With reference now to step 902 of Figure 9 and Figure 6, a communications protocol is utilized between system 1212 and the in-line substations to control their activity. Specifically, a standard semi equipment communications standard/generic equipment model (SECS/GEM) protocol may be used. Generally speaking, SECS is a



layer 6 protocol that describes the content of the messages while GEM is a higher layer application protocol that defines the messages themselves.

With reference still to step 902 of Figure 9 and Figure 6, the communications protocol is utilized to provide an interface between portions of the integrated in-line IC back-end manufacturing hardware 200. In another embodiment, the communications protocol may be established within each piece of hardware on line 200. As shown in Figure 6, the communications protocol results in a software hierarchy for line 200. In another embodiment, the software hierarchy is established to maintain overall control of line 200. Further, the communications protocol is independent of the hardware platform. Thus, compatible communication between any portion of line 200 is obtained.

With reference now to step 904 of Figure 9 and Figure 6, the present embodiment monitors a portion of line 200 using a manufacturing execution system (MES) 600 coupled with the communications protocol. Furthermore, MES 600 may be comprised of at least one equipment cell controller (CC). In the present embodiment, MES 600 may also be comprised of two CCs. Specifically, a portion of front-of-line hardware 300A is coupled with front-of-line equipment cell controllers (CC) 602, and a portion of end-of-line hardware 300B is coupled with end-of-line equipment CC 604. Both CC 602 and CC 604 are then coupled to communicate with MES 600 for command and control. In one embodiment, MES 600 maintains a

planning database 620 which includes a die-strip map database. In another embodiment, MES 600 controls the processing activities at each substation.

Accordingly, all lot movement and process-monitoring details are regularly updated to MES 600 and ultimately the planning database 620 via both CC 602 and CC 604. In

5 another embodiment, planning database 620 is further utilized to maintain an internal planning and/or order/shipment database. However, in order to maintain comprehensive tracking of lot movement and process-monitoring details, a system to differentiate each die-strip 400 is instituted. The specifics of the system to differentiate each die-strip 400 will be discussed in detail herein.

A further example of multiple embodiments of the software hierarchy is illustrated in Figure 13. Specifically, Figure 13 is a representation of the steps taken by the visual system, e.g., V/C 302, to view the die-strip 400. The results of their inspections are collected by CC 602 and CC 604 units and are then transferred to the central MES 600 system. In one embodiment, the inspection results are further transferred to database 620. In general the three columns (e.g. die-strips i, i+1, and i+2) represent portions of a die-strip 400 die map. Specifically, boxes F1-F8 represent mapping, while E1-E4 represent other parameters collected at other visual stations. All boxes represent process history information including individual die-strip map database (e.g. 620) and inspection (e.g. quality assurance (QA) 1 1310 and QA2 1320. 20 As stated herein, all data collected by V/C 302 systems is stored in a database that maintains each die-strip 400s' processing history. Although a specific hierarchy of

computer systems is established, the present embodiment is well suited to many types of computer system hierarchy. Additionally, the present embodiment of computer system hierarchy is illustrated for purposes of clarity, not as a means of limitation.

5

## REJECT MANAGEMENT

In one embodiment, reject management is a portion of the in-line assembly line back-end manufacturing process that utilizes the integrated software processes mentioned herein to determine the back-end manufacturing status, quality, and performance of each specific die on a die-strip 400. In general, aspects of reject management detailed herein allow comprehensive tracking and quality assurance of a die-strip 400 and every die thereon ensuring a high level of "out-the-door" product quality. Reject management is dependent on accurate V/C 302 calibration and integration with the software database 620.

With reference now to step 1002 of Figure 10 and Figure 5, the present embodiment implements an automated and database driven tracking process for die-strip 400 which uses the camera vision systems to automatically identify individual die-strips 400 and their respective locations as they traverse through the in-line assembly line 200. In one embodiment, the tracking process starts at die attach substation 304 and is maintained throughout the entire IC back-end manufacturing process. However, in order to maintain a die-strip level tracking

process, a two-dimensional code, known as data matrix 2D symbol 510 may be placed on every die-strip 400. In one embodiment, data matrix 2D symbol 510 is etched onto die-strip 400 by a laser. However any printing or affixing method could be used.

5

Specifically, each data matrix 2D symbol 510 utilizes a specialized 2D matrix code similar to a bar code. Data matrix 2D symbol 510 may store up to 19 characters, in one embodiment, which maintain all specific chip and lot related information. Further, a second data matrix 2D symbol 510 may also be placed on die-strip 400. This second data matrix 2D symbol 510 is analogous to the first data matrix 2D symbol 510 and may be utilized as a back up. Therefore, if any damage occurs to the first data matrix 2D symbol 510, the die-strip tracking process remains possible by utilizing back-up data matrix 2D symbol 510. In a second case, a combination of both first data matrix 2D symbol 510 and back-up data matrix 2D symbol 510 may be used for tracking recognition purposes.

With reference now to step 1004 of Figure 10 and Figure 6, the present embodiment accesses an electronic die-strip map database 620 that provides parameter storage for each individual IC component within each die-strip 400. In one embodiment, the electronic die-strip map database 620 is located in memory on MES 600. In general, the electronic die-strip map database 620 maintains a record of each die-strip 400 traversing the individual substations of the back-end

manufacturing process. Specifically, the electronic die-strip map database 620 maintains information relative to the die-strip level as well as information regarding inspection and processing at the individual die level.

5           An example of the electronic die-strip map database 620 is illustrated in Figure 4. Specifically, a single die-strip 400 is shown in a visual representation of the electronic die-strip map database 620. The database 620 records parameters for each chip on the die-strip 400 and these parameters are updated as the die strip traverses through the back-end manufacturing process thereby providing a process history for the die-strip 400. For instance, 164 individual die are illustrated on a matrix substrate, or leadframe, in an array-like structure on die-strip 400. On each die a representative letter is shown as a parameter within a designated die block. In one embodiment, the letter is either a G or a B. Specifically, G is a reference to good, while B is a reference to bad.

10           During the back-end manufacturing process, any changes to the status of a specific die are updated by the electronic die-strip map database 620. A negative update to the strip map would result in a change on die-strip 400 from a die block being designated with a G to a new designation of B. The designations of G and B are simplified examples of an actual electronic die-strip map database 620. Further, any representation resulting in differentiation between satisfactory and unsatisfactory die located on die-strip 400 may be utilized by the present

embodiment. A further example of differentiation is the parameter of test speed. For instance, the die-strip map database 620 could also categorize die based on performance data, such as speed, etc.

5           With reference now to step 1006 of Figure 10 and Figure 5, the present embodiment utilizes the tracking process to update the electronic die-strip map database 620 at each substation that collects parameter information throughout the back-end manufacturing process. Specifically, die-strip 400 is analyzed at each key process by V/C 302. In one embodiment, V/C 302 is used to inspect a portion of the die on die-strip 400 for physical attributes. Parameters are then updated for each die in the database 620. In another embodiment, V/C 302 is used as a data matrix 2D symbol 510 reader for location determination by identifying the die-strip 400. For example, the analysis of die-strip 400 in a front-of-line portion 300A is conducted by V/C 302. Further, the data matrix 2D symbol 510 on the same die-strip 400 is read by V/C 302. The results of both V/C 302 processes are reported to CC 602. CC 602 then passes the information to the electronic die-strip map database 620 located on MES 600. This information is then processed by the electronic die-strip map database 620. In so doing, the updated electronic die-strip map database 620 will continue to maintain a positive track of a portion of the die on die-strip 400.

20           Although in the present embodiment V/C 302 are used as a data matrix 2D symbol 510 reader, a distinct 2D code reader may be installed at the strip entry point

of a substation of processing equipment that will update and/or use the strip map database 620. The utilization of V/C 302 as the 2D code reader and die-strip 400 inspector are merely for purposes of brevity. It is further appreciated that each automated V/C 302 may be independent from, or in electronic communication with, any or all other automated V/C 302.

With reference still to step 1006 of Figure 10 and Figure 5, in the present embodiment V/C 302, the tracking process, and the electronic die-strip map database 620 are the tools that have improved the tracking, inspecting, and dehumanization of the IC back-end manufacturing process. Specifically, the reliability of V/C 302 in the electronic die-strip mapping process is important. V/C 302 is utilized for data matrix 2D symbol 510 reading and verification. For example, V/C 302 automatically recognizes the die-strip 400 by reading the data matrix 2D symbol 510 at different points throughout the in-line back-end manufacturing process. V/C 302 is further used for visually inspecting die-strip 400 and the die thereon throughout the in-line back-end manufacturing process. Specifically, the present embodiment uses V/C 302 inspection after some of the major process steps, for example, die attach substation 304, W/B substation 310, mold substation 314, SBA substation 318, and saw substation 320. In another embodiment, V/C 302 inspection is used after all of the major process steps. Accordingly, utilizing V/C 302 for both inspection of die-strip 400 and a portion of the die on die-strip 400, as previously stated, allows the present embodiment to replace human inspectors with automated inspection techniques.

As a result, completion times of the in-line assembly line process are markedly improved.

There are many reasons why automated inspection is preferred to human inspection. A major reason is the quantity of inspection capabilities. In the conventional process, initial human inspection is conducted on a portion of the batch. Each initial human inspection is then followed by a human QA inspection of a smaller portion of the same batch. This redundancy is established to ensure a quality product. However, in one embodiment of the present invention, all of the die on each die-strip 400 may be inspected. Thus, a complete inspection capability is obtained. Such a capability allows for higher product reliability.

A second reason for automation is the specific inspection method. In human inspection, each inspector brings a personality to the inspection process. Further, the inspection station has rotating personnel. Therefore, the inspection techniques differ per inspector. In an automated inspection process, no personality is involved and V/C 302 is in constant operation. Further, each V/C 302 is calibrated and all V/C 302 maintain a similar standard for inspection.

A third reason for automation over human inspection is the contact factor. For example, when a human inspects a batch, purposeful or incidental contact of either die-strip 400 or a die thereon may occur during the inspection process. With



an automated inspection system, there is no need for V/C 302 to make any sort of contact with die-strip 400 or any die thereon. Thus, all incidental damage caused by the inspector or the inspection is removed.

5           Therefore, it is appreciated that each of the preceding aspects of automated inspection result in an increase in productivity. Additionally, an increase in quality and quantity of product is realized due to better inspection practices. A further benefit is the reduction of collateral damage due to the removal of any incidental human contact.

10           With reference now to step 1008 of Figure 10 and Figure 6, the present embodiment categorizes the die on die-strip 400 based on information maintained by the electronic die-strip map database 620. Specifically, the electronic die-strip map is continuously updated at each inspection step, on the die-strip map server by V/C 302. Thus, the electronic die-strip map database 620 maintains the complete processing history of die-strip 400. This map database 620 can then be used to physically separate die into bins of similar categories.

15           Therefore, with reference to Figures 6 and 7, when die-strip 400 reaches saw  
20   substation 320 and sort substation 322, the electronic die-strip map is downloaded and the information is used to automatically sort and reject the designated "bad" units. Sorting may be performed based on any managed parameters. Specifically,

the reject management protocols utilize the electronic die-strip map database 620 categories and either accept or reject each die. In another embodiment, subsequent rejection processes take place following the testing, marking, and final visual inspection steps of the integrated in-line IC assembly method. At each rejection evaluation, accepted units continue the process while any rejected units are automatically placed in reject bins 610. Further, it is possible for the electronic die-strip map database 620 to isolate specific rejected units on die-strip 400 early in the in-line back-end manufacturing process such that no further IC back-end manufacturing processes are performed on the rejected units. In fact, rejected components, which are identified early in the back-end manufacturing process, remain in their rejected state on die-strip 400 until reaching sort substation 322. At that point, all rejected units are deposited in reject bins 610. Thus, valuable back-end manufacturing materials are saved for use on accepted units. In one embodiment, when a unit has passed all required evaluations and completed the tape and reel substation 328 of the in-line assembly process, the reel is then placed in a good bin 710.

With reference still to step 1008 of Figure 10, the present embodiment further utilizes the electronic die-strip map database 620 to establish a processing history for tracking material usage and equipment details, and preventing the mixing of chips. Another added benefit of having a processing history, are the improved defect analysis features. Specifically, the processing history may be used to isolate exact

areas within die-strip 400 or a substation of the integrated in-line IC back-end manufacturing process correlated with recurring defects. Thus, it is then possible to establish preventive maintenance techniques, such as, statistical process control (SPC) which predict and identify/repair these defective zones thereby increasing productivity.

### UNIVERSAL PACKAGING

In one embodiment, universal packaging is a portion of the in-line assembly line back-end manufacturing process which utilizes updated subassemblies mentioned herein in accordance with the integrated software processes disclosed. In general, aspects of universal packaging detailed herein allow package changeovers with minimal changeover times, thus allowing some amount of flexibility within package families. For example, an exemplary changeover in the entire line from a 7mm x 7mm package to any other package size may take less than thirty minutes.

With reference now to step 1102 of Figure 11 and Figure 6, an electronic die-strip map database 620 is accessed. Specifically, mold 314 of portion 300B is established as the introductory point, in process 650, for the universal packaging process. As stated above, mold 314 is the step in the IC back-end manufacturing process wherein the die above die-strip 400 is covered in a protective coating. In one embodiment, the protective coating is a type of plastic. Moreover, the protective coating is placed in a specific location on die-strip 400. That is independent of any

actual die shape. In fact, mold 314 is a standard process applied to each die-strip 400. As such, there is no need for modification of mold 314 process per specific die size run. Thus, any mechanical or manufacturing modifications required by mold 314 are reduced. Specifically, as long as the size of die-strip 400 remains constant, the size of the die on die-strip 400 is immaterial. In addition, die-strip 400 may utilize either plastic or copper as the strip portion for die attachment without any detrimental effects.

With further reference to process 1102 of Figure 11 and Figure 6, the integrated solder ball attach (SBA) substation 318 process is also universal. That is, in the present embodiment, SBA substation 318 process is independent of solder ball type. The specific choice is related to outside manufacturing costs and desired integrated chip requirements. In general, the integrated in-line IC back-end manufacturing process SBA substation 318 is similar in process to mold 314. That is, SBA substation 318 is also used at die-strip 400 level. Therefore, no matter what size die is above die-strip 400, SBA substation 318 uses the same universal attachment method. Because of the universality of SBA substation 318, there is no need to retool SBA substation 318 in order to process a different size die as long as die-strip 400 remains constant.

With reference now to step 1104 of Figure 11 and Figure 6, die-strip 400 is automatically cut based on information maintained by the electronic die-strip map

database 620. Specifically, due to the universality of both mold 314 and SBA 318 substations, die-strip 400 arrives at saw substation 320 in a uniform format. Saw substation 320 then requires specific instructions about the die specifications in order to cut die-strip 400 without damaging any individual die thereon. Specifically, saw substation 320 is informed of the specific cutting specifications by the electronic strip-map database 620. As stated above, the electronic strip-map database 620 maintains the complete strip processing history of die-strip 400. Hence, when saw substation 320 receives the cutting specifications, it is able to cut die-strip 400 into the specified components without any human interaction while maintaining the integrated assembly line IC back-end manufacturing format. The resulting cut die components are then individually packaged at T/R substation 328 using, in one embodiment, the industry standard quad flat packaging with no lead (QFN).

Thus, the present invention provides, in various embodiments, a method to integrate a IC back-end manufacturing assembly. Embodiments of the present invention also include a method to integrate a IC back-end manufacturing assembly which can proficiently perform IC back-end manufacturing in an in-line fashion. The present invention further provides a method to integrate a IC back-end manufacturing assembly which can curtail human visual inspection and QA process by using automated vision systems to maintain a higher quality of visual inspection. The present invention also provides a method to integrate an IC back-end manufacturing assembly which requires fewer personnel to maintain a back-

end manufacturing line. The present invention further provides a method to integrate an IC back-end manufacturing assembly which is compatible with existing IC back-end manufacturing processes.

5           The foregoing descriptions of specific embodiments of the present invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teaching. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the Claims appended hereto and their equivalents.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
221